


Router LTE Cat4 - FLT718		
Categoria	Especificações	Descrição
Basical Information	Modelo	FLT718
	Tipo	CPE
	Dimensões	172mm*168mm*52mm
	Peso	450g
	Cor	White
Imagens		
Interface Aérea	Padrões	Compatible with WCDMA, FDD-LTE 802.11 b/g/n
	Frequências	LTE FDD: B1, B3, B5, B7, B8, B28, B39TDD, B40TDD WCDMA: B1/2/4/5/8
	WIFI	RTL 8192, 2.4GHz, WIFI 2*2 MIMO, 802.11 b/g/n,
Performance	Maximum Data Throughput	LTE CAT 4 FDD-LTE 150Mbps/50Mbps
Hardware	Receive Diversity	Support Receive Diversity
	MIMO	Support DL 2x2 MIMO
	BB Chipset	Qualcomm MDM9207
	RF Chipset	Qualcomm WTR2965
	WiFi Chipset	RTL8192(802.11b/g/n)
	Memory	2Gb+2Gb or 4Gb+2Gb
	power consumption	<12W
	Power Voltage	DC12V/1A
	USIM/SIM	2FF SIM card support SIM/USIM/UIM,standard 6 PIN SIM card interface, support 3V SIM card and 1.8V SIM card;internal push-push SIM slot
	LED	Power Indication LED, WAN Signal Strength, WiFi/WPS Indication LED, WAN/LAN Status LED, Internet Status LED,
	USB	USB 2.0
	Antenna	Internal Antenna & External Antenna
	Buttons	POWER, Reset,WPS
	Slic	SI32185
	Ethernet	1WAN/LAN 10BaseT/100Base/1000Base automatic adaptive port
	RJ11	RJ11x1
	Reset	Pinhole
ESD	ESD Protection circuit; Contact±8KV、Air±10KV	
Battery	Not Support	
Software	SW Update	TR069 &Local Update
	WIFI Mode	AP
	WIFI Security	OPEN & WPA-PSK& WPA2-PSK & WPA-PSK/WPA2-PSK;
	USB Function	Support
	Voice	VoLTE & CS Domain voice
	IPv4	Support IPv4
	IPv6	Support IPv6
	Firewall	Mac/IP address filter, Port forwarding, WiFi Black/Whilte list
	Data Statistics	Support
	VPN Pass Through	PP2P/L2TP/IPSec
SIM Lock	Support	

	WAN Fallback to ETH	Manually
	HTTP	Support
Certificação ANATEL		04056-18-11492
Environment	Operating Temperature	Normal:-10°C to +65°C;
	Storage Temperature	-20° C to +85° C
	Humidity	5%~ 95%